

All-In-One



8500V Series

Desktop Replacement

Outstanding all-in-one design,
Excellent performance.



The 8500V series offers flexibility, modular design and plenty of power. This is the ultimate desktop replacement, the 8500V is always reliable, always cutting-edge and always flexible. When it comes to notebook performance, the 8500V is rewriting the road rules.

Superior Display	Unlimited Communication	Expandability	Power and Performance	Supreme Portability
15" XGA TFT, with 2X AGP 16MB SGRAM	Built-in LAN module and dealer optional 56K V.90 modem module	3-Spindle, with interchangeable CD-ROM/DVD-ROM /CD-RW drive	Intel Pentium III 933MHz, supports FC-PGA 370 package	Approximately 1.96" (50mm) thin and 9.25 lbs (4.2 Kg)

8500V Series Specification

Model	8500V Series
CPU	. Intel Pentium III 500/533/550/600/667/700/733/750/800/850/866/933MHz . Support FC-PGA 370 package
Core Logical	. VIA chipset
Display	. 15" XGA(1024x768) /SXGA+(1400x1050) TFT
Memory (RAM)	. DRAM upgradeable to 512MB , depend on 32/64/128/256MB SO-DIMM module . Two SO-DIMM sockets, support 3.3V Sync DRAM SO-DIMM(PC-100/PC-133)
Display Memory	. 16MB SGRAM
Video controller	. ATI Rage mobility . 3D graphics acceleration . 2X AGP support . Duoview display capability under windows 98 . Support TV-out and Video-in function
PCMCIA Slot	. Support CardBus, ZV port . Type II x2 or Type III x1
CD-ROM Drive (Removable)	. Built-in 24X CD-ROM . Interchangeable with DVD-ROM / CD-RW
FDD (Removable)	. Built-in 3.5" 1.44MB FDD . Interchangeable with 15mm(h) ZIP 100MB/250MB Drive / 2.5" 12.7mm(h) or 12.5mm 2nd HDD
HDD (Removable)	. Compatible with 2.5" 9.5mm(h)/12.7mm(h)/17.0mm(h) . Support DMA mode 2/ PIO mode 4 / ATA-33 / ATA-66 IDE HDD
Keyboard	. Multi-language, 101/102 Keys with numeric Keybad
Sound system	. AC97 compliant . Compatible with Sound Blaster Pro™ . HRTF 3D Positional Audio, DirectSound and DirectSound 3D acceleration . AC-3 virtualization . S/P DIF output for DVD content; . Built-in microphone . Built-in 2 watts and stereo speakers
I/O Ports	. 1xExternal (PS/2) keyboard & Mouse port / 1xIEEE1394 port / 1xSerial port / 1xParallel(ECP/SPP) port / 1xD-sub 15-pin CRT port / 1xS-video jack for TV output / 1xRCA jack for Video input / 2xUSB port / 1xTrackpad / 1xspeaker-out jack/1xline-in jack / 1xjack for microphone or S/P DIF output / 1x RJ-11 jack for 56K MDC modem / 1x RJ-45 jack for 100M/10M LAN / 1x 120-pin connector for port replicator / DC-in jack
Communication	. Wireless Infrared transfer : FIR(IrDA 1.1) . Built-in 10 Base-T/100 Base-TX alternative LAN module . Built-in 56K V. 90 MDC modem module
Power Management	. Support ACPI V 1.0B / Support APM V 1.2 / Soft Off / Device Power Management / CPU over temperature protection / Support suspend to disk / Battery low suspend / Resume from alarm time / modem ring (COM port only) / Smart fan control
Security	. Kensington® Lock
Battery	. Li-Ion smart battery
Dimension	. 358(w)x280(d)x50(h)mm, 14"x11"x1.96" . 4.2Kg, 9.25 lbs (with CD-ROM, FDD & Li-Ion battery)
Accessories & Options	. 8001 Li-Ion smart battery . 8006A Port Replicator . 8007 IO Mega 100MB ZIP drive . 800H 9000mAh Li-Ion smart battery . 800I IO Mega 250MB ZIP drive . 800D DVD-ROM drive 12.7mm height . 800E CD-RW drive 12.7mm height . 800F Software DVD player

The specification in gray is not yet available.
The content is subject to change without notice. Other brand and product names are trademarks and/or registered trademarks of their respective companies.